

| C Range - Undercounter          | C525WSD                                    |
|---------------------------------|--------------------------------------------|
| Width x Depth x Height mm       | 580x610x810mm                              |
| Feet Height                     | 10mm-20mm                                  |
| Basket size                     | 500x500mm                                  |
| Maximum useable height          | 340mm                                      |
| Door Opening                    | 365mm                                      |
| Cycle times                     | 90/120/150 Seconds                         |
| Water consumption per cycle     | 2.0 Litres                                 |
| Wash tank capacity              | 20 Litres                                  |
| Phase - Options                 | Single/3-Phase                             |
| Power – Single Phase Options    | 2.6kW(13Amp),4.5kW(20Amp),<br>6.5kW(30Amp) |
| Power – Three Phase             | 6.5kW(16Amp)                               |
| Detergent pump                  | Peristaltic - non timed                    |
| Rinse aid pump                  | Peristaltic - non timed                    |
| Drain pump                      | Yes                                        |
| Breaktank                       | Yes                                        |
| Water supply pressure           | 2 to 4 Bar                                 |
| Body Construction               | Partial Double Skin                        |
| Door/Hood Construction          | Double Skin                                |
| Scrap Trays                     | Yes                                        |
| Internal Rinse Booster Pump     | Yes                                        |
| Number Of Cycles                | 3                                          |
| Total Maximum Load(as supplied) | 6.5kW(30Amp) - Single Phase                |