

## HTY615DUK



### NEW PRODUCT

Professional hood type dishwasher, double skinned hood, 600 x 500mm or 500 x 500mm basket

|                            |                            |
|----------------------------|----------------------------|
| Product Family             | Dishwashers                |
| Type                       | Hood Type Dishwasher       |
| Line                       | TOPLINE                    |
| Basket dimensions          | 600 x 500mm or 500 x 500mm |
| Outside dimensions (WxDxH) | 716 x 760 x 1520/2040mm    |

### TECHNICAL SHEET

#### TECHNICAL DATA



Structure: Single skinned in AISI 304 stainless steel and insulated

Required electrics and fuse protection: 3ph 10kW 20A / 1ph 7kW 32A

Control type: Electronic soft touch controls

WRAS compliant break tank: Yes

Basket dimensions: 600 x 500mm or 500 x 500mm

Baskets per hour: 60 / 40 / 24 / 20

Number of programs: 7

Thermo-acoustic insulation: hood

Rinse aid dispenser: Peristaltic pump with electronic adjustment via the control panel

Detergent dispenser: Peristaltic pump with electronic adjustment via the control panel

Useable loading height: 420mm

Wash tank capacity: 25L

Boiler capacity: 8L

Boiler heating element: 9kW 3ph / 6kW 1ph

Wash tank heating element: 2.2kW

Inlet water maximum temperature: 60°C

Outside dimensions (WxDxH): 716 x 760 x 1520/2040mm

Power supply / Total power installed: 400V 3N 50Hz / 10kW - 230V 1N 50Hz / 7kW

Weight (net/gross): 124 / 136kg

Integral continuous water softener: no

Wash system: Wash pump with 'Soft start' system

Wash pump: 1kW

Rinse system: Atmospheric boiler and rinse pump (HTR system)

Drain system: Drain pump and triple stage dynamic filter with partial water exchange in the wash tank

Filtering system: Integral stainless steel top wash tank filter with removable scrap basket and additional micro filter in the sump for wash pump protection

Water consumption per cycle: 3.2L

Selectable: FRESH WATER function for complete wash tank water replacement after each wash cycle

Selectable: EXTENDED-RINSE function for a prolonged rinse

Dishwasher capable of washing 1/1 GN trays and boxes 600x400mm

Double skinned and insulated hood

Thermostop for controlling the rinse water temperature

Self-diagnosis system with fault warning

Insulated boiler

Drain pipe on the boiler for complete drainage

'Stand-by' function of the heating elements during periods of non-use

2 x wash arms in AISI 304 stainless steel

2 x rinse arms in AISI 304 stainless steel

Moulded tank with rounded corners

Connection to water mains with a 3/4 threaded fitting on the back of the appliance

Self cleaning cycle available as standard

Cycle automatically starts when closing the door/hood (optional)

Adjustable feet

## ACCESSORIES

[PB60D01](#) - Plastic asket for dishes, max 22 pieces Ø 250mm

[PB60G01](#) - Plastic universal flat-bottomed basket

[WB60D01](#) - Wire basket for 24 dishes Ø 260mm

[WB60G01](#) - Wire fine-mesh flat-bottomed basket

[PHOOS01](#) - Plastic single cutlery basket

[PHOOS02](#) - Plastic cutlery basket with 6 compartments

[PHOOS03](#) - Plastic cutlery basket with 8 compartments

[KITSONLIV](#) - Retro-fit low level chemical sensor kit for all Topline glass and dishwashers

## EQUIPMENT

1 [PB60D01](#) - Plastic asket for dishes, max 22 pieces Ø 250mm

- 1 [PB60G01](#) - Plastic universal flat-bottomed basket
- 1 [PHOOS03](#) - Plastic cutlery basket with 8 compartments

Do you need more information about this product? Contact us and we will reply to you as soon as possible.

[CONTACT US](#)

